

Shaking Incubator

BS-1E

- ◆ Microprocessor control temperature and timer
- ◆ LCD display temperature, speed and timer
- ◆ Stainless steel inner, with door lock
- ◆ stepless shaking speed adjustable
- ◆ The glass door is convenient for observation
- ◆ The interior lighting is convenient for observation

Scope of application:

- ◆ BOD culture, seed-breeding test
- ◆ Thermostatic microorganism, plant cultivation

SHTR-140

- ◆ Microprocessor control temperature and timer
- ◆ LCD display temperature, speed and timer
- ◆ Stainless steel inner,
- ◆ stepless shaking speed adjustable, brushless motor driver
- ◆ The glass window is convenient for observation.
- ◆ With power module failure, motor stall, Hall error, bus voltage undervoltage, overvoltage, communication failure alarm function

Safety Mechanism:

- ◆ Over temperature alarm, Finished work alarm



Model	BS-1E	BS-2F
Capacity	140L	280L
Temperature range	5-50℃	5-50℃
Temperature accuracy	±1℃	±1℃
Shaking speed	Start up ---300rpm	Start up---300rpm
Amplitude	20mm(Orbital)	20mm(Orbital)
Shaking groups	1	2
Bottles capacity	Tube ∅ 16x200,△100mlx15,△200mlx9	(Tube ∅ 16x200,△100mlx15,△200mlx9)x2
Heating power	300W	400W
Compressor power	130W	180W
Timer	0-9999min	0-9999min
Voltage	220V 50Hz	220V 50Hz
Dimension(mm)	570x590x1100	1140x600x1100
Package(mm)	640x700x1310	1230x700x1200
G.W./N.W.	90/62kg	160/110kg

Model	SHTR-140	SHTR-280
Capacity	140L	280L
Temperature range	4-60℃	4-60℃
Temperature accuracy	±0.5℃	±0.5℃
Shaking speed	Start up ---300 rpm	Start up---300 rpm
Amplitude	20mm(Orbital)	20mm(Orbital)
Tray size	Tube ∅ 16x200,△100mlx15,△200mlx9	(Tube ∅ 16x200,△100mlx15,△200mlx9)x2
Heating power	300W	400W
Compressor power	200W	400W
Timer	0-9999min	0-9999min
Voltage	220V 50Hz	220V 50Hz
Dimension(mm)	600x630x1150	1180x630x1150
Package(mm)	700x730x1250	1280x730x1250
G.W./N.W.	105/75kg	190/135kg



BS-1E

SHTR-140