



## URIT-610 / URIT-600 Coagulation Analyzer



CE







### Excellent Performance

- Advanced dual-magnetic circuit bead method
- Multi detectors up to different parameters analysis
- Multi-channel random & reliable hemostasis



### Easy Operation

- Mini-reagent consumption, open reagent system
- 5.1-inch LCD screen, keyboard input
- Internal thermal recorder



### Accurate Result

- Advanced method to eliminate interference from hemolysis, chyle, turbidity, plasma viscosity etc.
- Stable incubator temperature



### 24h Professional Technical Support

- 24 x 7 around the clock response
- Entire life cycle service solution
- Door-to-door service for complicated problems



### Reliable Spare Parts quality

- Well-know spare parts supplier
- High performance PCB board
- Individual quality control management for each single component

<b>Principle</b>	dual-magnetic circuit bead method
<b>Parameters</b>	PT(Prothrombin Time) APTT(Activated Partial Thromboplastin Time) TT(Thrombin Time) FIB(Fibrinogen) Protein C, Protein S, HEP(High-molecular-weight Heparin) LMWH(Low-molecular-weight Heparin) LA(Lup us Anticoagulant) Thrombin factor II, V, VII, X, VIII, IV, IX, XI, XII etc.
<b>Detector</b>	4-channel / 2-channel
<b>Incubator</b>	16 sample positions, 4 reagent positions(tunable incubation time)
<b>Data storage</b>	500 test results
<b>Display</b>	5.1" LCD screen
<b>Print</b>	Built-in printer & external printer
<b>Input / Output</b>	RS-232 port and parallel interface
<b>Ambient</b>	work temperature: 15~35°C; relative humidity: ≤80%RH
<b>Power</b>	AC100V~240V, 50/60Hz, 45W
<b>Dimension</b>	380mm x 40 mm x 130mm
<b>Weight</b>	About 5.9kg