

Reagent Card Incubator

BGC-24

- ◆ LED display, temperature and time parameters can be set
- ◆ Microprocessor control temperature, time, temperature control linear, small fluctuation
- ◆ Safe to use, reliable performance, automatic timing and alarming
- ◆ Simple and generous appearance, transparent cover, experiment process at a glance
- ◆ Two independent incubators, automatic timing, mutual interference, each incubator can store 12 cards at the same time, fast and efficient sample processing
- ◆ Can be used for blood type reagent card heating constant temperature function



BGC-24

ZENJ-II

Model	BGC-24
Temperature range	RT+5-50℃
Timer	1-99min59s
Precision	±0.5℃
Heating time(20-37℃)	≤5min
Power	200W
Voltage	220V 50Hz
Dimension(mm)	280x380x115
Package(mm)	340x440x160
G.W./N.W.	12/10kg

Plasma Extractor

ZENJ-II

- ◆ For blood stations, hospitals and other units to separate the use of plasma
- ◆ After bags in the blood is layered
- ◆ Points pulp clamp pressure can make the different composition of blood top-down being squeezed out.heating constant temperature function

Model	ZENJ-II
Clamping force	20N
Apply bags	100 ml, 200 ml, 300 ml, 400 ml
Dimension(mm)	165x250x250
Package(mm)	230x300x300
G.W./N.W.	3/2.5KG

Blood Collection Minitor

BMC-1200A

- ◆ Function of load-bearing, Blood bag weight deducted and Liquid production control.
- ◆ Functions of pallet swing, alarm, proximity control, swing stop and swing automatic recovery
- ◆ Eliminates the man-made error and provides convenience for the production of plastic bags
- ◆ Suitable for various blood sampling mechanism

BMC-1200B

- ◆ For blood stations, hospitals and other units to separate the use of plasma
- ◆ After bags in the blood is layered
- ◆ Points pulp clamp pressure can make the different composition of blood top-down being squeezed out.heating constant temperature function



BMC-1200A

BMC-1200B

Model	BMC-1200A	BMC-1200B
Range	0-1200ml	0-1200ml
Division value	1ml	1ml
Liquid production rate	0.5--3ml/s	0.5--3ml/s
Liquid production error	±5%	±5%
Liquid specific gravity	1.05g/mL	1.05g/mL
Oscillation frequency	30-32rpm	30-32rpm
Swing angle	13±2	13±2
Power	40W	40W
Alarm and block	Sound light alarm and block	Sound light alarm and block
Block applied piping	---	external diameter: Ø3~Ø6mm, thickness: 0.5mm
Block thrust	--	≤14N
Voltage	110V 60Hz/ 220V 50Hz	110V 60Hz/ 220V 50Hz
Dimension(mm)	220x170x160	275x230x210
Package (mm)	290x240x210	350x300x260
G.W./N.W.	3/2.5kg	5.5/5kg