



# Incubator

## Biochemical Incubator

### SPX-150B/SHP-150-D

- ◆ Microprocessor control temperature and timer
- ◆ LCD display temperature and running timer
- ◆ Stainless steel inner, with door lock
- ◆ The glass door is convenient for observation.
- ◆ Over temperature alarm
- ◆ Automatic alarm after operation.
- ◆ BOD culture (optional interior with socket)

### Scope of application:

- ◆ Environmental protection, health and epidemic prevention, drug testing, agriculture, livestock, fisheries and other scientific research, universities, production departments.



Model	SPX-50B	SPX-100B	SPX-150B	SPX-250B	SPX-500B
Capacity	50L	80L	186L	250L	500L
Heating power	100W	100W	142W	242W	350W
Compressor power	124W	124W	200W	200W	800W
Temperature accuracy	±0.5℃	±0.5℃	±1℃	±1℃	±1℃
Temperature range	5-60℃				
Timer	0-9999min				
Voltage	220V 50Hz				
Dimension(mm)	480x570x920	480x570x950	550x530x1630	610x540x1700	900x710x1830
Package(mm)	580x630x1140	580x630x1180	650x620x1720	710x650x1800	1000x810x1900
G.W./N.W.	46/36kg	48/38kg	88/60kg	105/70kg	220/165kg

Model	SHP-150-D	SHP-250-D	SHP-300-D
Capacity	186L	250L	300L
Heating power	250W	300W	350W
Compressor power	400W	600W	800W
Temperature accuracy	±1℃	±1℃	±1℃
Temperature range	-10~60℃	-10~60℃	-10~60℃
Timer	0-9999min	0-9999min	0-9999min
Voltage	110V 60Hz / 220V 50Hz	110V 60Hz / 220V 50Hz	110V 60Hz / 220V 50Hz
Dimension(mm)	550x530x1630	610x540x1700	610x540x1700
Package(mm)	650x620x1720	710x650x1800	750x680x1850
G.W./N.W.	88/60kg	105/70kg	118/82kg