



Table Top Steam Sterilizer



Use

The table type sterilizers are safely auto-controlled, which are designed for the dental clinics, hospitals, school lab, scientific research institutions and laboratory. And mostly suitable for sterilizing of surgical, dental and eye instruments, glassware medicine, culture medium and biological dressing, food, etc.

Characteristics

- ◆ Indicator light indicates working state.
- ◆ For 4~6 minutes rapidly sterilizing.
- ◆ Sterilizing temperature and time can be preset.
- ◆ Steam-water inner circulation system: no steam discharge, and the environment for sterilizing will be clean and dry.
- ◆ Over temperature & over pressure auto-protection.
- ◆ Safe protection of water lacking.
- ◆ Exhaust the cool air automatically.
- ◆ With three stainless steel sterilizing plates.
- ◆ The chamber of the sterilizer is made of stainless steel.
- ◆ Automatically shut off with beep reminding after sterilization.

Technical Data

MODEL	TM-XB20J	TM-XB24J
Technical Data		
Sterilizing chamber volume	20L φ 250 × 420mm	24L φ 250 × 520mm
Working pressure	0.22MPa	
Working temperature	134℃	
Temperature adjust range	105~134℃	
Timer range	0~60min	
Heat average	≤ ± 1℃	
Power	1.5KW / AC220V.50Hz(AC110V.60Hz)	
Sterilizing plate(mm)	340 × 200 × 30(3piece)	400 × 200 × 30(3piece)
Dimension(mm)	480 × 480 × 384	580 × 480 × 384
Exterior package dimension(mm)	700 × 580 × 500	800 × 580 × 500
G.W/N.W	44kg / 40kg	50kg / 45kg