

Table Top Steam Sterilizer















Use

The table type sterilizers are safely auto-controlled, which are designed for the dental clinics, hospitals, school lab, scientific research institutions and laboratory. And mostly suitable for sterilizing of surgical, dental and eye instruments, glassware medicine, culturemedium and biological dressing, food, etc.

Characteristics

- ◆ For 4~6 minutes rapidly sterilizin.
- ◆ Digital display of working status, touch type key.
- ◆ With 3 fixed cycles of sterilizing program and adjustable for user.
- The whole process of water adding, temperaturerising, sterilizing, drying steam discharging controlled automatically.
- Steam-water inner circulation system: no steam discharge, and the environment for sterilizing will be clean and dry.
- Safe protection of water lacking.
- ◆ Exhaust the cool air automatically.
- ◆ Door safety lock system.
- ◆ With four stainless steel sterilizing plates.
- ◆ The chamber of the sterilizer is made of stainless steel.
- ◆ Automatically shut off with beep reminding after sterilization.
- ◆ With drying function.

Technical Data

MODEL Technical Data	TM-XD20D	TM-XD24D
Sterilizing chamber volume	18L	23L φ 250 × 470mm
Working pressure	0.22MPa	
Working temperature	134℃	
Temperature adjust range	105~134℃	
Timer range	0~99min	
Heat average	≤ ± 1°C	
Power	1.5KW/AC220V.50Hz	2KW/AC220V.50Hz
Sterilizing plate(mm)	340 × 200 × 30(3piece)	400 × 200 × 30(3piece)
Dimension(mm)	480 × 680 × 455	480 × 680 × 455
Exterior package dimension(mm)	580×780×580	580×780×580
G.W/N.W	53kg / 48kg	54kg / 49kg