



# Intelligent Blast Drying Oven

Model ZHG9000 series



## Characteristics

- ◆ The chamber of the blasting oven is made up of superior stain steel sheet or the mirror-finish stainless steel sheet, and the outside sprayed with plastic power, double-decked tempered glass-observation, with handsome appearance, and it is safe and convenient to operate on.
- ◆ The blasting oven is controlled by the microcomputer, equipped with temperature setting testing, double digital display and PID self-setting function.
- ◆ Equip with over-temperature auto-protection & time setting, undulatory property is small.
- ◆ The blasting oven is equipped with following alarming function, churned-up hot air circle, low heat age lose, blasting and heating can be separately operated.
- ◆ Hot air circle system is made up of exit fans and suitable fan duct with low noisy, the temperature in the chamber is uniformity.

## Technical Data

MODEL Technical Data	ZHG-9040A(S)	ZHG-9070A(S)	ZHG-9140A(S)	ZHG-9240A(S)	ZHG-9640A(S)
Power supply				AC220V.50Hz	
The range of temperature			50~300°C		
Heat average			± 1°C		
Followed-alarming			+5°C		
Power	1000W	1500W	2000W	2500W	4500W
Chamber dimension(mm)	350 × 350 × 350	450 × 350 × 450	550 × 450 × 550	600 × 500 × 750	800 × 800 × 1000
Dimension(mm)	500 × 560 × 705	650 × 560 × 805	750 × 660 × 905	800 × 710 × 1105	1000 × 1010 × 1355

Annote: A—the inner chamber is made up of galvanized sheet.

AS—the inner chamber is made up of mirror-finish stain steel sheet.